



PRODUCT SPECIFICATION

VERTICAL CONVEX ELBOW 90°



| G.S. | △ (kg/m) | G.C. | △ (kg/m)** | A (mm) | ≡ (uni.) |
|----------|----------|----------|------------|--------|----------|
| CX9S0310 | 0,54 | CX9G0310 | 0,59 | 100 | 1 |
| CX9S0315 | 0,66 | CX9G0315 | 0,72 | 150 | 1 |
| CX9S0320 | 0,78 | CX9G0320 | 0,86 | 200 | 1 |
| CX9S0330 | 0,65 | CX9G0330 | 0,72 | 300 | 1 |
| CX9S0610 | 0,73 | CX9G0610 | 0,80 | 100 | 1 |
| CX9S0615 | 0,85 | CX9G0615 | 0,93 | 150 | 1 |
| CX9S0620 | 0,97 | CX9G0620 | 1,07 | 200 | 1 |
| CX9S0630 | 1,21 | CX9G0630 | 1,33 | 300 | 1 |
| CX9S0640 | 1,46 | CX9G0640 | 1,61 | 400 | 1 |
| CX9S0650 | 1,71 | CX9G0650 | 1,88 | 500 | 1 |
| CX9S0660 | 1,94 | CX9G0660 | 2,14 | 600 | 1 |

| G.S. | △ (kg/m) | G.C. | △ (kg/m)** | A (mm) | ≡ (uni.) |
|----------|----------|----------|------------|--------|----------|
| CX9S0810 | 0,87 | CX9G0810 | 0,95 | 100 | 1 |
| CX9S0815 | 0,99 | CX9G0815 | 1,09 | 150 | 1 |
| CX9S0820 | 1,12 | CX9G0820 | 1,23 | 200 | 1 |
| CX9S0830 | 1,37 | CX9G0830 | 1,50 | 300 | 1 |
| CX9S0840 | 1,63 | CX9G0840 | 1,79 | 400 | 1 |
| CX9S0850 | 1,84 | CX9G0850 | 2,03 | 500 | 1 |
| CX9S0860 | 2,08 | CX9G0860 | 2,29 | 600 | 1 |
| CX9S1010 | 1,05 | CX9G1010 | 1,15 | 100 | 1 |
| CX9S1015 | 1,16 | CX9G1015 | 1,27 | 150 | 1 |
| CX9S1020 | 1,47 | CX9G1020 | 1,61 | 200 | 1 |
| CX9S1030 | 1,63 | CX9G1030 | 1,68 | 300 | 1 |
| CX9S1040 | 1,79 | CX9G1040 | 1,97 | 400 | 1 |
| CX9S1050 | 2,01 | CX9G1050 | 2,21 | 500 | 1 |
| CX9S1060 | 2,45 | CX9G1060 | 2,70 | 600 | 1 |

| EDITION DATE | EDITION N° |
|--------------|------------|
| 2016/06 | 1 |

ACCORDING TO UNE-EN 61537-2007

SENDIZIMIR GALVANISATION ACCORDING TO UNE-EN 10346:2010.
HOT DIP GALVANISED ACCORDING TO UNE-EN ISO 1461:2010

CHARACTERISTICS OF INSTALLATION

THE INSTALLATION OF THIS PRODUCT WILL BE CARRIED OUT
ACCORDING TO THE R.E.B.T.

- COPY NO CONTROLLED. THIS INFORMATION COULD BE MODIFIED BY AISCAN WITHOUT PREVIOUS NOTICE.