



# PRODUCT SPECIFICATION

## AISCAN RHF

| TYPE          | COMPOSITION                  | Ø OUT<br>mm | TOLER.<br>ANCE.<br>mm | Ø INS.<br>mm | LENGTH<br>m | TOLER.<br>mm | THREAD  | THREAD<br>LENGTH<br>MM. | SLEEVES | LABELS | TUBES<br>MALLET | Nº TIES |
|---------------|------------------------------|-------------|-----------------------|--------------|-------------|--------------|---------|-------------------------|---------|--------|-----------------|---------|
| AISCAN-RHF-16 | HALOGEN FREE<br>TERMOPLASTIC | 16          | +0 -0,3               | 10,5         | 3000        | +10 -5       | M16X1,5 | 12,5 +3-0               | 1       | 1      | 19              | 3       |
| AISCAN-RHF-20 | “                            | 20          | +0 -0,3               | 14           | 3000        | +10 -5       | M20X1,5 | 14 +3-0                 | 1       | 1      | 19              | 3       |
| AISCAN-RHF-25 | “                            | 25          | +0 -0,4               | 18           | 3000        | +10 -5       | M25X1,5 | 17 +3-0                 | 1       | 1      | 19              | 3       |
| AISCAN-RHF-32 | “                            | 32          | +0 -0,4               | 24,5         | 3000        | +10 -5       | M32X1,5 | 19 +3,5-0               | 1       | 1      | 10              | 3       |
| AISCAN-RHF-40 | “                            | 40          | +0 -0,4               | 31,5         | 3000        | +10 -5       | M40X1,5 | 21 +4-0                 | 1       | 1      | 10              | 3       |
| AISCAN-RHF-50 | “                            | 50          | +0 -0,5               | 40,5         | 3000        | +10 -5       | M50X1,5 | 23 +4,5-0               | 1       | 1      | 5               | 3       |
| AISCAN-RHF-63 | “                            | 63          | +0 -0,6               | 52           | 3000        | +10 -5       | M63X1,5 | 25 +4,5-0               | 1       | 1      | 5               | 3       |
| EDITION DATE  | EDITION NUMBER               | CARD NUMBER |                       |              |             |              |         |                         |         |        |                 |         |
| 2014/05       | 5                            | FT-RHF      |                       |              |             |              |         |                         |         |        |                 |         |

| CHARACTERISTICS ACCORDING TO STANDARD<br>IEC 61386-21 |                |
|-------------------------------------------------------|----------------|
| CODE:                                                 | 442212540010   |
| CRUSHING STRENG:                                      | >1250 N        |
| IMPACT RESISTANCE:                                    | >6J at -5°C    |
| OPERATING TEMPERATURE RANGE:                          | -5+90°C        |
| RIGID                                                 | YES            |
| DIELECTRICAL RIGIDITY:                                | >2000 V        |
| ISOLATION RESISTANCE:                                 | >100 MOhm      |
| EXTERNAL INFLUENCES:                                  | IP54           |
| FLAME PROPAGATE:                                      | NO             |
| COLOUR:                                               | GREY RAL. 7035 |

| CHARACTERISTICS LABEL                                                                                                                                           |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>Each label indicates:</i>                                                                                                                                    |
| Type, nominal, number of meter, standard UNE-EN applied, “CE” marked, storage and use instructions, Bar code EAN-13, date, control number and manufacture line. |
| EACH TUBE BAR INDICATES: type, nominal, standard UNE-EN applied, code, date, hour, manufacture line and “CE” marked.”                                           |

| ACCESORY TUBE                            |
|------------------------------------------|
| <b>TYPE “AISCAN-MR” HALOGEN<br/>FREE</b> |

ACCORDING TO STANDARD UNE-EN 50267-2-2 [old UNE-21-147(2)/IEC-754(2)] about “Determination of the degree of acidity of gases for materials by measuring pH and conductivity”.  
ACCORDING TO STANDARD UNE-EN 21031-15:2008 “Determination of halogens. Elementary test”.

**- NO CONTROLLED COPY. THIS INFORMATION COULD BE MODIFIED BY AISCAN WHITOUT PREVIOUS ADVERTISMENT-**