



PRODUCT SPECIFICATION

AISCAN TEIC

TYPE	COMPOSITION	Ø OUT mm	TOLER- ANCE mm	Ø INS. mm	LENGTH m	TOLER. mm	Nº SPIRAL	SPIRAL SEQUENCE	LAYERS	RADIUS MIN. CURVATURE mm	Nº TIES
AISCAN-TEIC-20	RIGID PVC	20	+0 -0,3	13,4	100	+2 -1	77	9-8-9-8-9-8-9-8-9	9	60	4
AISCAN-TEIC-25	RIGID PVC	25	+0 -0,4	18,5	75	+2 -1	56	8-8-8-8-8-8-8	7	75	4
AISCAN-TEIC-32	RIGID PVC	32	+0 -0,4	24,3	50	+2 -1	39	7-6-7-6-7-6	6	96	4
EDITION DATE	EDITION NUMBER	CARD NUMBER									
2015/09	02	EP-TEIC									

CHARACTERISTICS ACCORDING TO STANDARD IEC 61386-22	
CODE:	332122540010
CRUSHING STRENG:	>750 N
IMPACT RESISTANCE:	>2J at -5°C
OPERATING TEMPERATURE RANGE:	-5+60°C
CURVABLE	YES
DIELECTRICAL RIGIDITY:	>2000 V
ISOLATION RESISTANCE:	>100 MOhm
EXTERNAL INFLUENCES:	IP54
FLAME PROPAGATE:	NO
COLOUR:	PURPLE-BROWN- GREEN-WHITE- BLACK-BLUE

CHARACTERISTICS LABEL
<i>Each label indicates:</i>
Type, nominal, number of meter, standard UNE-EN applied, "CE" marked, storage and use instructions, Bar code EAN-13, date, control number and manufacture line.

ACCESORY TUBE
TYPE "AISCAN-MP" C/ GREY

- NO CONTROLLED COPY. THIS INFORMATION COULD BE MODIFIED BY AISCAN WHITOUT PREVIOUS ADVERTISMENT.-