



PRODUCT SPECIFICATION

AISCAN TMR

TYPE	COMPOSITION	Ø OUT. mm	TOLER- ANCE mm	Ø INS. ± TOL. mm	Ø INS. EFFECT.	LENGTH mm	TOLER. mm	THREAD	LENGTH THREAD MM	TUBES MALLET	LABELS
AISCAN-TMR-16	STEEL	16	+0 -0,3	13,6	12,5	3000	+10 -5	M16X1,5	12,5 +3	19	1
AISCAN-TMR-20	"	20	+0 -0,3	17,6	16,5	3000	+10 -5	M20X1,5	14 +3	10	1
AISCAN-TMR-25	"	25	+0 -0,4	21,5	21	3000	+10 -5	M25X1,5	17 +3,5	10	1
AISCAN-TMR-32	"	32	+0 -0,4	29,2	28	3000	+10 -5	M32X1,5	19 +3,5	7	1
AISCAN-TMR-40	"	40	+0 -0,4	37,2	36	3000	+10 -5	M40X1,5	19 +4	5	1
AISCAN-TMR-50	"	50	+0 -0,5	47,2	46	3000	+10 -5	M50X1,5	20 +4,5	5	1
AISCAN-TMR-63	"	63	+0 -0,6	59,6	58,2	3000	+10 -5	M63X1,5	22 +4,5	3	1
EDITION DATE	EDITION NUMBER	CARD NUMBER									
2013/06	5	EP-TMR									

CHARACTERISTICS ACCORDING TO STANDARD UNE-EN 61386-21

CODE:	555711542010
CRUSHING STRENGTH:	>4000 N
IMPACT RESISTANCE:	>20,4J at -45°C
OPERATING TEMPERATURA RANGE:	-45 +400°C
RIGID:	YES
EXTERNAL INFLUENCES:	IP 54
FLAME PROPAGATE:	NO
COLOUR:	ZINC
NON CORROSIVE INTERIOR PAINT	

CHARACTERISTICS LABEL

Each label indicates:

Type, nominal, number of meters, standard UNE-EN applied, "CE" marked, Storage and use instructions, Bar code EAN-13, date, control number and manufacture line.

EACH TUBE BAR INDICATES: type, nominal, standard UNE-EN applied, code, date, hour, manufacture line and "CE" marked.

ACCESSORY TUBE

**MTMR
(SHUTTER UNIONS)**

- NO CONTROLLED COPY. THIS INFORMATION COULD BE MODIFIED BY AISCAN WHITOUT PREVIOUS ADVERTISMENT.-